

Product datasheet

Specifications



APC Back-UPS CS 650VA, 230V, 4 IEC outlets (1 surge)

BK650-AS

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	400 W
Rated power in VA	650 VA
Plug standard	IEC 60320 C14
Nb of power socket outlets	3 IEC 60320 C13 1 IEC 60320 C13 surge
Cable length	1.83 m
Number of cables	2
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD 1 x detachable 1.2 m IEC power cord 1 x detachable 1.8 m IEC power cord Telephone cable USB cable Warranty card

General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Beige
Height	16.5 cm
Width	9.1 cm
Depth	28.4 cm
Net weight	6.04 kg

Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Input voltage limits	160...282 V adjustable 180...260 V

Output

Maximum configurable power in W	400 W
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Maximum configurable power in VA	650 VA

Conformance

Product certifications	A-Tick C-Tick CE GOST NEMKO
Equipment protection policy	Lifetime : \$100000 Lifetime : 50000 GBP

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	5...95 %
Operating altitude	0...30000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...4572.00 m
Acoustic level	45 dBA
Heat dissipation	0 Btu/h

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	1
Battery charger power	12 W rated
Battery power in VAh	95 VAh runtime
Battery life	4...6 year(s)
Extended runtime	0

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	320 J
Data line protection	RJ45 analog phone line for phone/fax/modem/DSL

Packing Units

Package 1 Weight	7.32 kg
Package 1 Height	49.4 cm
Package 1 width	18.5 cm
Package 1 Length	41.5 cm
SCC14	10731304224430
Number of Units in Package 2	1
Package 2 Weight	7.30 kg
Number of Units in Package 3	48

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------